


MALE THREADED ADAPTOR



	Size	Code	g	SP	A	B	C	E	L
1	20mmx1/2"	MTA20X050BKA	225	72	51	45	21	20	
2	25mmx3/4"	MTA25X075BKA	60	150	79	57	53	27	20
3	32mmx1"	MTA32X100BKA	91	85	93	65	65	34	24
4	40mmx1 1/4"	MTA40X125BKA	196	40	112	85	82	44	25
5	50mmx1 1/2"	MTA50X150BKA	258	25	124	97	93	54	28
6	63mmx2"	MTA63X200BKA	465	16	157	122	117	64	42

Note : SP - Standard Packing Quality, g - Individual fitting weight in gms

Kimplas Compression fittings PN 16 and are designed to use with all types of Polyethylene Pipes i.e. HDPE, MDPE and LDPE (grades PE100, PESO, PE63, PE 25 etc.). Unique design of the fitting facilitates insertion of the pipe into fitting without disassembling the fitting. The working temperature range of the fittings is - 5° to+ 40°C and the fittings are recommended for cold water services only. The fittings are ideally suited for Drip and Sprinkler Irrigation piping networks.

Standards:

Pipe compatibility ISO:4427-2, EN:12201-2,IS:4984,DIN:8074,IS:12786
Dimensions, Features & Functional Tests:ISO:3501,ISO:3503,ISO:3459
Threading: IS:554, ISO:7/1, BS:21, DIN:2999
Complies with ISO:14236

Common Applications:

For connecting Sprinkler Irrigation mains, sub-mains and laterals
For connecting Drip Irrigation mains and sub-mains.
For connecting fertigation equipment like Venturi, Fertilizers Tank and Dozing pump
Enables speedy laying of Pipes in Emergencies and ideal for semi permanent Sprinkler Systems

Installation :

Joint preparation must be done as specified in the installation instructions. Pipe ends must be cut square and burr-free before using with the fittings. Chamfer may be provided on the pipe end to facilitate ease of pipe insertion. To install the fitting, there is no need to open the nut and other components of the fitting. To install the fitting, just loosen the nut by three to four turns, insert the pipe into the fitting until the pipe crosses the rubber seal and stops at the pipe stop. Then tighten the nut by hands only. For fittings of size 40 mm and above a wrench recommended by Kimplas may be used for additional tightening. The nut should be closed tightly, however there is no need for the nut to actually meet the body. Complete Installation Manual may be downloaded.

Advantages :

The body is made of Polypropylene and designed with modular construction and axial reinforcement
The nut made of Polypropylene, with its sturdy design holds the pipe-fitting assembly intact with continuous working pressures upto 16 Bars
The grip ring made up of POM (Poly-acetal) prevents the pipe being pulled out from the fitting
The PP (Packing Pressure) Bush exerts thrust on the rubber O'- Ring/ Gasket, compresses on pipe and fitting body to ensure leak-tightness
Rubber O'-Ring / Gasket prevent leakage under internal pressure as well as under external pressure as in case of vacuum and/or suction
Plastic and rubber materials conform to the Standard requirements for use with irrigation water
For connecting to BSP threaded GI Pipe and fittings and brass/ PVC valves etc
Higher penetration of Pipe in the fittings enables for proper alignment
Clearance-Fit for ease of installation and repairs
Tolerance fit to take care of ovality of coiled pipes
Permanent Batch Indicator, Size, PN rating and Raw Material Grade marking for ease of traceability
Compact but sturdy design for ease of installation and trouble free service