


COMPRESSION FEMALE THREADED ADAPTOR(FTA) METAL SS304



	Size	Code	g	SP	A	B	C	E	L
1	20mmx $\frac{1}{2}$ "	CMFTA20X050BLA	75	125	77	53	45	21	20
2	25mmx $\frac{3}{4}$ "	CMFTA25X075BLA	144	75	84	60	53	27	23
3	32mmx1"	CMFTA32X1 00BLA	202	40	99	74	65	34	31

Note : SP - Standard Packing Quality, g - Individual fitting weight in gms

Kimplas Compression fittings PN 16 and are designed to use with all types of Polyethylene Pipes i.e. HOPE, MOPE (grade PE100, PE80, PE63, etc.). Unique design of the fitting facilitates insertion of the pipe into fitting without disassembling the fitting.

The working temperature range of the fittings is - 5° to + 40°C and the fittings are recommended for cold water services only. The fittings are ideally suited for connecting House Service Connections in Drinking Water Distribution piping networks. For exact recommendations on the applications and use, refer Kimplas Technical Specifications Manual.

Standards:

Pipe compatibility ISO :4427-2, EN:12201-2, IS: 4984, DIN: 8074
Dimensions, features & functional tests: ISO:3501, ISO:3503, ISO:3459
Threading: IS:554, ISO:7/1, BS:21, DIN:2999
Complies with ISO:14236

Common Applications:

For jointing PE pipe to threaded metal pipe or fittings during pipe-laying.
Pipe connections in areas difficult to access in narrow trenches
Repairing localized damages on pipes Connections Pipe Connections of permanently laid down (immovable) pipes
Enables speedy laying of Pipes in emergencies and ideal for semi permanent Water Supply Systems

Installation :

Joint preparation must be done as specified in the installation instructions. Pipe ends must be cut square and burr-free before using with the fittings. Chamfer may be provided on the pipe end to facilitate ease of pipe insertion. To install the fitting, there is no need to open the nut and other components of the fitting. To install the fitting, just loosen the nut by three to four turns, insert the pipe into the fitting until the pipe crosses the rubber seal and stops at the pipe stop. Then tighten the nut by hands only. For fittings of size 40 mm and above a wrench recommended by Kimplas may be used for additional tightening. The nut should be closed tightly, however there is no need for the nut to actually meet the body. Complete Installation Manual may be downloaded.

Advantages :

The body is made of Polypropylene and designed with modular construction and axial reinforcement
The nut made of Polypropylene, with its sturdy design holds the pipe-fitting assembly intact with continuous working pressures upto 16 Bars
The grip ring made up of POM (Poly-acetal) prevents the pipe being pulled out from the fitting
The PP (Packing Pressure) Bush exerts thrust on the rubber O'-Ring/ Gasket, compresses on pipe & fitting body to ensure leak-tightness
Rubber O'-Ring/ Gasket prevent leakage under internal pressure as well as under external pressure as in case of vacuum and/or suction
Plastic & rubber materials conform to the Standard requirements for use with potable water for human consumption
Connecting to BSP threaded GI Pipe & Fittings and Brass/PVC valves/ Water Meters etc
Corrosion resistant SS 304 Metal insert for sturdy joint with metal pipes/fittings and valve/water meters
Higher penetration of Pipe in the fittings enables for proper alignment
Clearance-Fit for ease of installation and repairs
Tolerance fit to take care of ovality of coiled pipes
Permanent Batch Indicator, Size, PN rating and Raw Material Grade marking for ease of traceability
Compact but sturdy design for ease of installation & trouble free service